

Product Name: SUPER SEATONE Burnt Umber
Code Number: 11B632
Vehicle Type: Surfactant Blend
Solvent: Water / Propylene Glycol
Color Index Name: Br-7
Suggested for Industrial Finishes ? Yes

Product Line Description: Aqueous pigment dispersions for in-plant tinting of Industrial and Architectural Coatings

Super Seatone® aqueous dispersions are designed to be easy to use, free flowing, viscosity stable pigment concentrates. They are tightly controlled for consistent color characteristics when added by weight.

TYPICAL PROPERTIES

Lbs/gal	11.2
Wt % Pigment	35.0
Vol % Pigment	13.5
Wt % Vehicle Solids	9.5
Vol % Vehicle Solids	12.0
Wt % Volatile	55.5
Vol % Volatile	74.5
VOC g/l *	148
VOC lb/gal *	1.2
% Propylene Glycol by Wt.	3.0
% Propylene Glycol by Vol.	4.0

EXTERIOR DURABILITY

(1= Poor, 5 = Excellent)

MASSTONE	5
TINT	5

CHEMICAL RESISTANCE

(1= Poor, 5 = Excellent)

Aliphatic	5
Aromatic	5
Ketone	5
Ethyl Acetate	5
Ethyl Alcohol	5
Cellosolve	5
DB Phthalate	5
Glycol	5
Dilute Acid	5
Dilute Alkali	5
Soap	5

HEAT RESISTANCE

(1= Poor, 5 = Excellent)

150 C - 15'	5
150 C - 30'	5

* Note - For aqueous products, VOC is calculated minus water.