# **TECHNICAL DATA SHEET**

YIPIN<sup>®</sup> Iron Oxide Pigment Iron Oxide Red 4125



Edition of2015-12-04TypeRed pigmentDelivery FormPowderChemical ClassSynthetic iron oxide alpha-Fe2O3Color IndexPigment red 101(77491)CAS No.1309-37-1Use RecommendationCoating, Construction, Plastic

COLOR VALUES AND TINTING STRENGTH				
Reference			Standard	
	<u>Min</u>	<u>Max</u>	Test Method	
Reduction with titanium dioxide (1:5)	R-706		Similar to ASTM D-387	
△ <b>L*</b>	-0.7	+0.7		
∆a*	-0.7	+0.7		
<b>△b*</b>	-0.7	+0.7		
△E*ab		1.0		
Binder	R-05			
Relative tinting strength [%]	98.0	103.0	Similar to ASTM D-387	

TECHNICAL DATA			
	<u>Min</u>	<u>Max</u>	Test Method
Water-Soluble Content [%]		0.5	ASTM 1208-96
Sieve Residue (0.045mm) [%]		0.05	ASTM D 185
Fe <sub>2</sub> O <sub>3</sub> [%]	95.0		ASTM D 50
PH Value	5.0	7.0	ASTM 1208-96
Moisture (After Production) [%]		1.0	ASTM D 280-01
Loss on Heating 1000 ℃ 1/2 h [%]		4.0	ASTM D1208
Particle Shape	Spherical		Electron Micrographs

 YIPIN PIGMENTS, INC.
 Tel:+1-909-243-7394
 Fax: +1-909-243-7397
 www.yipin.com

 一品颜料
 Tel:+86-21-5950 8509
 Fax: +86-21-5950 7893
 wh@yipin.com

### TECHNICAL DATA SHEET

# YIPIN® Iron Oxide Pigment Iron Oxide Red 4125



	Approx.	
Predominant Particle size [µM]	0.2	Electron Micrographs
Water Absorption [g/100g]	$\sim$ 25	ASTM D 28
Tamped Density [g/ml]	~1.0	ASTM D153
Density [g/ml]	∼ <b>5.0</b>	ASTM D153 C604

STANDARD PACKAGING	50lb/bag
STANDAND FACINAGING	Julu/bag

#### TRANSPORT AND STORAGE

Protect against weathering. Store in a dry place and avoid extreme fluctuations in temperature. Special conditions for opened packaging: Close bags after use to prevent the absorption of moisture and contamination.

#### SAFETY

The product is not classified as dangerous under the relevant EC directives and corresponding national regulations valid in the individual EU member states. It is not dangerous according to transport regulations. In countries outside the EU, compliance with the respective national legislation concerning the classification, packaging, labeling and transport of dangerous substances must be ensured.

The information contained in the safety data sheet should be observed.

This contains information on handing, product safety and ecology.

This information is given in good faith, without warranty. It is also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General conditions of sale and delivery.