

**Product Name:** INDUSTRIAL Line Phthalo Green BS  
**Code Number:** 42A400  
**Vehicle Type:** Medium - Short Oil Alkyd  
**Solvent:** Aliphatic 140  
**Color Index Name:** G-7  
**Suggested for Industrial Finishes ?** Yes

**Product Line Description:** Flushed and Dispersed pigments for Industrial and Architectural finishes.  
 "Industrial" short to medium oil alkyd dispersions are designed to be free flowing, viscosity stable pigment concentrates. They are tightly controlled for consistent color characteristics when added by weight.

### TYPICAL PROPERTIES

Lbs/gal	8.3
Wt % Pigment	20.9
Vol % Pigment	10.1
Wt % Vehicle Solids	30.4
Vol % Vehicle Solids	27.3
Wt % Volatile	48.7
Vol % Volatile	62.6
VOC g/l *	483
VOC lb/gal *	4

### CHEMICAL RESISTANCE

(1= Poor, 5 = Excellent)

Aliphatic	5
Aromatic	5
Ketone	5
Ethyl Acetate	5
Ethyl Alcohol	5
Cellosolve	5
DB Phthalate	5
Glycol	5
Dilute Acid	5
Dilute Alkali	5
Soap	5

### EXTERIOR DURABILITY

(1= Poor, 5 = Excellent)

MASSTONE	5
TINT	5

### HEAT RESISTANCE

(1= Poor, 5 = Excellent)

150 C - 15'	5
150 C - 30'	5

\* Note - For aqueous products, VOC is calculated minus water.