COADIS™ 173

Dispersing agent for water-borne systems **Ionic Copolymer dispersant**

TYPICAL CHARACTERISTICS

Nature Appearance Solid Content (%) Active Content (%) pH Brookfield viscosity (mPa.s) Specific gravity Neutralization type Solvent Polyacrylic acid Pale yellow aqueous solution 30 30 10 < 350 1.21 Sodium Water

DESCRIPTION

Coadis[™] 173 is a versatile polyacid dispersing agent imparting an excellent performance accross a wide range of waterborne paint formulations. It is designed for flat to semi-gloss paints, anticorrosion paints, caulks and sealants and other formulations showing high rates of mineral pigments and requiring a limited water absorption. Also suitable for oxide pigments and more specifically zinc oxides.

RECOMMENDED ADDITION LEVEL

The typical dosage should be selected in the range from 0.5% to 1.0% (dry on total pigment weight).

STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- 220L Drum
- Bulk

HANDLING & STORAGE

It should be protected from the effects of weathering and stored between 5 and 40°C.

Once opened, packaging should be resealed immediately after use. In these conditions, this product should be used within 12 months from delivery.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKET

Coatings & Inks

- Architectural Coating
- Graphic Arts
- Industrial Coating
- Textile & Leather Coating
- Traffic Paint

Adhesives & Sealants

- Assembly
- Other Adhesives
- Sealants

KEY BENEFITS

FORMULATION

• Compatibility	
• Easy handling	
 Ready to use 	
STORAGE	
 Antisettling 	
 Syneresis resistance 	
 Floating resistance 	
 Viscosity stability 	
FILM PROPERTIES	
 Stain resistance 	
 Transparency 	
Water resistance	
 APEO free Bacteria resistance Heavy metal free Solvent-free 	Yes Yes Yes Yes
PVC	
PVC High	
PVC Mid	
PVC Low	

SUITABLE FOR

Fillers	
Inorganic pigments	

2023-06-02 Page 1/1



Please consult Arkema's disclaimer regarding the use of our products on www.arkema.com/en/products/product-safety/disclaimer