

# **Technical Data Sheet**

# EPON™ Resin 3002

## **Product Description**

EPON™ Resin 3002 is a low viscosity solid epoxy resin designed for use in electrical encapsulating powders. It is also designed to have better sintering or blocking stability than EPON Resin 3001.

# Application Areas/Suggested Uses

- · Electrical encapsulating powders
- Any use requiring a low viscosity solid resin

#### **Benefits**

- · Relatively low melt viscosity
- Improved blocking stability compared to EPON Resin 3001
- Good reactivity in typical electrical powder formulations
- · Excellent wet-out of pigments and fillers
- · Low hydrolyzable chloride for electrical applications

### Sales Specifications

Property	Value	Unit	Test Method
Color	500 max	Pt-Co	ASTMD1544
Viscosity at 25°C	7.4 - 9.5	сР	ASTMD1545
Weight per Epoxide	520 - 590	g/eq	ASTMD1652

#### **Typical Properties**

Property	Value	Unit	Test Method
Density	1.18	g/cc	ASTMD1209
Viscosity Melt	6-8	Р	ASTMD2196

#### Safety, Storage & Handling

Please refer to the MSDS for the most current Safety and Handling information.

Please refer to the Hexion web site for Shelf Life and recommended Storage information.

Exposure to these materials should be minimized and avoided, if feasible, through the observance of proper precautions, use of appropriate engineering controls and proper personal protective clothing and equipment, and adherence to proper handling procedures. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheet (MSDS) for these and all other products being used are understood by all persons who will work with them. Questions and requests for information on Hexion Inc. ("Hexion") products should be directed to your Hexion sales representative, or the nearest Hexion sales office. Information and MSDSs on non-Hexion products should be obtained from the respective manufacturer.

### Packaging

EPON Resin 3002 Generated: May 24, 2022

http://www.westlakeepoxy.com/en-US/product/epon-resin-3002

Revision: 9/1/2007 12:00:00 AM

 $\ensuremath{\mathbb{R}}$  and  $\ensuremath{^{\text{TM}}}$  Licensed trademarks of Westlake Inc.

The information provided herein was believed by Westlake Inc. ("Westlake") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Westlake Epoxy are subject to Westlake Epoxy's terms and conditions of sale. WESTLAKE MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY WESTLAKE, except that the product shall conform to Westlake's specifications. Nothing contained herein constitutes an offer for the sale of any product.

Available in bulk and drum quantities.

#### **Contact Information**

For product prices, availability, or order placement, please contact customer service:

www.hexion.com/Contacts/

For literature and technical assistance, visit our website atwww.hexion.com

EPON Resin 3002 Generated: May 24, 2022

http://www.westlakeepoxy.com/en-US/product/epon-resin-3002

Revision: 9/1/2007 12:00:00 AM

Issue Date:

® and ™ Licensed trademarks of Westlake Inc.

The information provided herein was believed by Westlake Inc. ("Westlake") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Westlake Epoxy are subject to Westlake Epoxy's terms and conditions of sale. WESTLAKE MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY WESTLAKE, except that the product shall conform to Westlake's specifications. Nothing contained herein constitutes an offer for the sale of any product.