

Dispersing agent especially designed for titanium dioxide
Ionic Copolymer dispersant

Typical Characteristics

Specific gravity	1.18
Nature	Polycarboxylate in aqueous solution, ammonium salt
Appearance	Pale yellow aqueous solution
Solid Content (%)	44
Active Content (%)	44
pH	7
Neutralization type	Ammonium
Solvent	Water

Description

Coadis™ 144 A is a universal pigment dispersant which provides outstanding performance across a broad spectrum of waterborne exterior and interior coating formulations. It exhibits excellent stability and compatibility and is designed to enable maximized gloss potential while providing ideal viscosity, flow and wet adhesion from flat to high gloss systems.

Recommended addition level

The typical dosage should be selected in the range from 0.5% to 1.0% (active on total pigment formulation weight). It is important to determine the proper level for the finished paint application. If too low a level is incorporated, the dispersion may be incomplete leading to underperformance with regards to hiding, stability, and a grind will not maximize gloss.

Standard Packaging

Other packaging may be available upon request

- 1000L IBC
- 220L Drum
- Bulk

Handling & Storage

It should be protected from the effects of weathering and stored between 5 and 40°C. Once opened, packaging should be resealed immediately after use. In these conditions, this product should be used within 12 months from delivery.

Processing instructions

COADIS™ 144 A must be incorporated before the pigments and fillers addition. COADIS™ 144 A can be used in combination with rheology modifiers within the Coatex line (COAPUR™ and RHEOTECH™).

Health and environmental data

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact Coatex.

Coatings And Inks

- Architectural Coating
- Graphic Arts
- Industrial Coatings
- Textile And Leather Coating

Key Benefits

Formulation

- **Compatibility**
- **Cost in use**
- **Easy handling**

Storage

- **Antisettling**
- **Floating resistance**
- **Viscosity stability**

Film Properties

- **Hiding power/Opacity**
- **Anticorrosion**
- **Gloss**

Other

- **APEO free**
- **Heavy metal free**
- **Solvent-free**

PVC

PVC Low	●●●●○
PVC Mid	●●●●○
PVC High	●●●●○

Suitable for

Fillers	●●●●○
Organic pigments	●●○○○
Inorganic pigments	●●●●●