

Revised 5/25/2017

Product Name:	BLACK SHIELD [®] Black Aqueous Dispersion		
Code Number:	11B045		
Vehicle Type:	Aqueous Acrylic		
Solvent:	Water		
Color Index Name:	Bk-7		
Suggested for Industrial Finishes ?	Yes		
	Carbon Black Dispersion of Medium - High Jetness affording excellent coverage, gloss and stability.		
Product Line Description:	Pigment dispersions in an acrylic vehicle for use in a wide variety of aqueous systems.		
	Black Shield® aqueous dispersions are designed to be easy to use, free flowing, viscosity stable pigment concentrates. They are tightly controlled for consistent color characteristics when added by weight.		

TYPICAL PROPERTIES

CHEMICAL RESISTANCE

Lbs/gal	10.2	(1= Poor, 5 = Excellent)	(1= Poor, 5 = Excellent)	
Wt % Pigment	39.0	Aliphatic	5	
Vol % Pigment	26.5		5	
Wt % Vehicle Solids Vol % Vehicle Solids	15.7 17.5		5 5	
		,	5	
Wt % Volatile	45.3		5	
Vol % Volatile	56.0		5 5	
VOC g/l *	7	,	5	
VOC lb/gal *	<0.1		5 5	
		Soap	5	
EXTERIOR DURABILITY		HEAT RESISTANCE		
(1= Poor, 5 = Excellent)		(1= Poor, 5 = Excellent)		
MASSTONE	5	150 C - 15'	5	
TINT	5	150 C - 30'	5	

* For aqueous products, VOC is calculated minus water

DyStar Hilton Davis 2235 Langdon Farm Rd. Chininnati, OH 45237 USA Telephone +1 800-477-1022 Fax (marketing) +1 513 441 3771 DyStar-USA@DyStar.com www.DyStar.com This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to check its validity and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale and Delivery.



DyStar Hilton Davis 2235 Langdon Farm Rd. Chininnati, OH 45237 USA Telephone +1 800-477-1022 Fax (marketing) +1 513 441 3771 DyStar-USA@DyStar.com This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to check its validity and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale and Delivery.