# ECODIS™ C 30

Dispersing agent for water-based systems

# Ionic Homopolymer dispersant

#### **TYPICAL CHARACTERISTICS**

Nature Polyacrylate sodium salt

Appearance Colourless to slightly yellow, clear liquid

### **DESCRIPTION**

Ecodis™ C 30 has been especially developed as a lighter colored version of Ecodis™ P 30 with limited color evolution upon storage. It ensures the complete dispersion of extenders and inorganic pigments at high solids contents in systems showing medium to high PVC.

# **RECOMMENDED ADDITION LEVEL**

The required amount varies from 0.1% to 0.5% of active ingredients based on the total weight of the pigments and fillers. A more easy way is to start formulation trials using 0.4% to 0.5% of it, as delivered, on the total formulation weight. It is recommended to disperse the pigments in a pH range between 7.0 and 9.5.

# STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- 220L Drum
- Bulk

# **HANDLING & STORAGE**

It should be protected from the effects of weathering and stored between 5 and 40°C. Once opened, packaging should be resealed immediately after use.

In these conditions, this product should be used within 12 months from delivery.

#### **PROCESSING INSTRUCTIONS**

Ecodis™ C 30 should be preferably added to water before the pigment incorporation. The optimum level is determined for each pigment blend by plotting the graph of the viscosities of the pigment dispersion in water, versus the amount of dispersant. The level of dispersant corresponding to the minimum viscosity is chosen.

# **HEALTH AND ENVIRONMENTAL DATA**

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

#### **MARKET**

#### **Coatings & Inks**

- Architectural Coating
- Graphic Arts
- Textile & Leather Coating
- Traffic Paint

#### **Adhesives & Sealants**

- Assembly
- Other Adhesives
- Sealants

# **KEY BENEFITS**

#### **FORMULATION**

- Cost in use
- Compatibility
- Easy handling

#### **STORAGE**

- Antisettling
- Viscosity stability
- Floating resistance
- Syneresis resistance

# FILM PROPERTIES

- Hiding power/Opacity
- Gloss

••••

Yes

Yes

Yes

Yes

- APEO free
- Bacteria resistance
- Heavy metal free
- Solvent-free

# PVC

PVC High PVC Mid

PVC Low

# **SUITABLE FOR**

Inorganic pigments Fillers



2023-06-14

Page 1/1

