

TECHNICAL DATASHEET

Liquid Coating Resins and Additives

ADDITOL XL 6509/100

PRELIMINARY PRODUCTINFORMATION

TYPE

Wetting and dispersing agent for solvent-containing systems

FORM OF DELIVERY (f.o.d.)

Active substance

100 %

DEVELOPMENT PRODUCT

This product, serving for trial purposes only. Deviations which might occur during transfer into manufacturing in a commercial scale are possible and do not constitute any material defect.

TENTATIVE PRODUCT DATA

Determined per batch:

Colour / Appearance VLN 250

colour cless-slightyel appearance clear

Dynamic Viscosity DIN EN ISO 3219

dynamic viscosity [mPa.s] 400 - 600

(100 1/s; 23 °C)

Acid Value DIN EN ISO 2114

acid value [mg KOH/g] 90 - 110

(f.o.d)

Not continually determined:

Density (Liquids) DIN EN ISO 2811-2

density [g/cm³] 1,08

approx. (20 °C)

Flash Point (Pensky-Martens) DIN EN ISO 2719

flash point [°C] 125

approx.

SPECIAL PROPERTIES AND USE

Additol XL 6509/100 is a low molecular weight additive, which is especially able to deflocculate and stabilize inorganic pigments very actively by electrical charging at the pigment surface and permits very low viscosity millbase formulations.

Due to the high wetting power of Additol XL 6509/100 coatings/inks with high gloss and improved colour strength can be achieved. It decreases settling of pigments/extenders and offers good levelling.

In consequence of its acidic character Additol XL 6509/100 is also recommended for the use in metallic formulations since it shows very good stabilization of aluminium flakes.

It is also qualified for the production of highly concentrated matting agent pastes.

Additol XL 6509/100 should be added in the grinding step. Quantity to be added: 0.3 - 3% on pigment / extender and matting agent.

STORAGE

At temperatures up to 25 $^{\circ}\text{C}$ storage stability packed in original containers amounts to at least 730 days.

REMARK:

Data contained in this publication are based on careful investigations (and are intended for information only). Due to scale up of this product there is not yet sufficient experience concerning serial production. We can therefore not exclude, that based on future knowledge product data and other indicated properties in upcoming Technical Data Sheets will be subject to change. We reserve the right to leave the product name unchanged, even if product data or other indicated properties will vary from the present product info. Regardless of the data contained in this publication any user is obliged to carry out tests under his own responsibility as to the suitability of the product for a particular use and to investigate the possible violation of industrial property rights of third parties. Information is therefore not binding and cannot be construed as guaranteeing specific properties of products. We apply our General Sales Conditions.

1.0/14.11.2013