



PRODUCT CODE **P2HD/9/3.5/RP/AS-22**

**PAILSAVER™ INSERT FOR PLASTIC PAILS**

**PRODUCT DESCRIPTION:** The P2HD/9/3.5/RP/AS-22, is a rigid, durable, tapered, seamless, vacuum-formed insert designed specifically for 2-gallon plastic pails. This robust insert is molded from FDA-approved high-density polyethylene, which provides better resistance to many solvents, compared to LDPE. A contoured lip snaps over the top bead to prevent leakage between the insert and the pail wall.

**Insert Specifications**

**MATERIAL USED**

High-density polyethylene

**INSERT DIMENSIONS**

Diameter: 9.125" (+0.25/-0")

Height: 8.875" (+/-0.125")

Average thickness: 15 mil (+/-10%)

**WEIGHT**

1.6 oz. (+/-10%)

**SIDE-WALL DESIGN**

Straight-sided (taper)

**TEMPERATURE PARAMETERS**

High (momentary): 180° (240°)F

Low: -20° F

**ANTI-STAT**

Standard: NFPA-99

Resistivity rating: 10<sup>11</sup> Ω/Sq. typical

**Packaging Specifications**

**CARTON WEIGHT**

18 lbs.

**CARTON DIMENSIONS**

Length: 21"

Width: 21"

Height: 22"

**QUANTITY/CASE**

100

**PACKAGING STYLE**

Nested

CDF's ANTI-STAT LINERS CONTAIN AN INTERNAL ANTI-STAT AGENT THAT IS INTENDED AS AN AID TO REDUCTION OF STATIC BUILD-UP. THEY ARE NOT DESIGNED AS, AND SHOULD NOT BE USED AS, THE PRIMARY CONTROLLER OF STATIC ELECTRICITY IN A PROCESS. CDF'S ANTI-STAT LINERS SHOULD NOT BE USED IN ELECTRO-STATIC COATING SYSTEMS OR OTHER HIGHLY VOLATILE AREAS. PLEASE CONSULT YOUR SAFETY ENGINEER, SAFETY CONSULTANT, OR CDF IF THERE IS ANY QUESTION AS TO APPROPRIATENESS OF USE.

**TYPICAL APPLICATIONS:** The P2HD/9/3.5/RP/AS-22 is perfect for containing all liquids, powders and pastes that can be contained in high-density polyethylene, as well as resist long-term exposure to a wide range of materials. The anti-stat additive helps to reduce static build-up in static sensitive applications compatible with high-density polyethylene such as paints, volatile materials and fine powders.

CDF warrants that its products will be free from defects in material and workmanship for one-hundred eighty (180) days after the date of delivery. Warranty claims must be made in writing no later than five (5) business days after the expiration of the warranty period. CDF's obligations under this warranty are limited solely to replacement of such products as are proven to be defective after CDF's inspection. **Prior to use, the user shall independently determine the suitability of the products for the user's intended use and user assumes all risk and liability whatsoever in connection therewith. CDF products are intended for single use application. Any reuse of the liner and/or fitment voids this warranty.** CDF EXPRESSLY DISCLAIMS AND EXCLUDES ANY AND ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE RELATING TO THE USE OR PERFORMANCE OF CDF PRODUCTS. CDF SHALL NOT BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE UNLESS CAUSED SOLELY BY CDF'S NEGLIGENCE. CDF SHALL NOT BE LIABLE FOR LOSS OF PROFIT OR OTHER SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OF CDF PRODUCTS, REGARDLESS OF THE LEGAL THEORY ON WHICH THE CLAIM IS BASED AND EVEN IF CDF HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

**CDF CORPORATION • 77 Industrial Park Road • Plymouth, MA 02360  
(800) 443-1920 • fax (508) 747-6333 • www.cdf1.com**

Specifications subject to change without notice.  
Product Specification: P2HD/9/3.5/RP/AS-22  
Revision: H  
7/28/14