

## TECHNICAL DATA SHEET

# SYNOCURE® 9268 BA 80

(Formerly CHEMPOL® 317-7168)

Acrylic polyol

### PRODUCT APPLICATION DETAILS

SYNOCURE® 9268 BA 80 is a high solids, hydroxyl functional acrylic with low isocyanate demand and 2.8 VOC capability, with good adhesion, flexibility, and gloss retention, and long pot life, for cost-effective coatings.

### SALES SPECIFICATIONS

	CHARACTERISTICS	METHODS
Solid content	79 - 81 %	-
Viscosity	Z4-Z6 Gardner Holdt	-
Reduced viscosity (60% in n-Butyl Acetate)	E-G	-
Color	4 Gardner	-
Acid value	10 max mg KOH/g	-

### OTHER CHARACTERISTICS<sup>1</sup>

	CHARACTERISTICS	METHODS
Solvent	n-Butyl acetate	-
Density	8.7	-
Hydroxyl content	1.7 %	-
Hydroxyl number	56	-

<sup>1</sup>The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

### MARKETS

#### Coatings & Inks

- Industrial Coating
  - Automotive - OEM
  - General Industry
  - Protective Coating
  - Protective And Marine Coating

# SYNOCURE® 9268 BA 80

(Formerly CHEMPOL® 317-7168)

## PRODUCT SAFETY

Please refer to the corresponding Safety Data Sheet.

## STORAGE AND HANDLING

SYNOCURE® 9268 BA 80 should be stored indoors in the original, unopened and undamaged container, in a dry place at a temperature not exceeding 30°C. Exposure to direct sunlight should be avoided.

In the above mentioned storage conditions the shelf life of the resin will be from the shipping date.

**Headquarters: Arkema France**  
51, Esplanade du Général de Gaulle  
92800 Puteaux – France  
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.  
Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

**ARKEMA**