

## TECHNICAL DATA SHEET

## SYNOLAC® 9739 (Formely CHEMPOL® 211-2339)

Oil free polyester

## **PRODUCT APPLICATION DETAILS**

SYNOLAC® 9739 is a high solids polyester with excellent adhesion, exterior durability, and color retention, that provides flexibility in 2K urethane coatings.SYNOLAC® 9739 is compatible with thermoset acrylic resins and can be used as a modifier to reduce VOC.

## **SALES SPECIFICATIONS**

	CHARACTERISTICS	METHODS
Solid content	94 %	-
Viscosity	Z5-Z6+ Gardner Holdt	-
Reduced viscosity (70% in Xylene)	C-E	-
Color	2 Gardner	-
Acid value	6 mg KOH/g	-

## OTHER CHARACTERISTICS<sup>1</sup>

	CHARACTERISTICS	METHODS
Solvent	Xylene	-
Density	9.3 lbs/gal	-
Hydroxyl content	0.3 %	-
Hydroxyl number	240	-

<sup>&#</sup>x27;The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

## **MARKETS**

## **Coatings & Inks**

- Industrial Coating
  - General Industry
  - Protective And Marine Coating

## **PERFORMANCE BENEFITS**

- Excellent adhesion
- Good exterior durability
- Excellent color retention



# SYNOLAC® 9739 (Formely CHEMPOL® 211-2339)

## **FORMULATION GUIDELINES**

#### **RECOMMENDATIONS OF USE**

Provides flexibility in 2K urethane coatings. Metal – General purpose high performance enamel. Modifier to reduce VOC.

## **PRODUCT SAFETY**

Please refer to the corresponding Safety Data Sheet.

#### **STORAGE AND HANDLING**

SYNOLAC® 9739 - Packaged products should be stored in a dry indoor location. The material should be stored in the original, unopened and undamaged container at storage temperatures not exceeding 85° F (30° C). Exposure to direct sunlight should be avoided. For assistance with the best practices for bulk shipment storage and handling contact Arkema.

**Arkema Coating Resins** 410 Gregson Dr. Cary, NC 27511 – USA T +1 919 469 6700

**Headquarters: Arkema France** 51, Esplanade du Général de Gaulle 92800 Puteaux – France T +33 (0)1 49 00 80 80

